



Advanced Micro Ring Resonator Filter Technology

G. Lenz and C. K. Madsen
Lucent Technologies, Bell Labs

APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

REVIEW OF THIS MATERIAL DOES NOT IMPLY DEPARTMENT OF
DEFENSE INDORSEMENT OF FACTUAL ACCURACY OR OPINION

All-Pass Filters



$$|H(\omega)| = 1$$

$$\phi(\omega) = \text{arbitrary}$$



- ◆ Phase equalization
- ◆ Dispersion compensation
- ◆ Optical delay line

Single stage APF



APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

REVIEW OF THIS MATERIAL DOES NOT IMPLY DEPARTMENT OF
DEFENSE INDORSEMENT OF FACTUAL ACCURACY OR OPINION



Mathematical Form

$$H(\omega) = \prod_{n=0}^{N-1} \frac{e^{j\omega} - z_n}{e^{j\omega} z_n^* - 1} = \prod_{n=0}^{N-1} \frac{e^{j\omega} - r_n e^{j\theta_n}}{e^{j\omega} r_n e^{-j\theta_n} - 1}$$

$$|H(\omega)| = 1$$

$$\phi(\omega) = \sum_{n=0}^{N-1} \text{Arg} \left[\frac{e^{j\omega} - z_n}{e^{j\omega} z_n^* - 1} \right]$$




Phase equalization without
amplitude distortion



Group Delay

$$\tau(\omega) = \sum_{n=0}^{N-1} \frac{\sinh \chi_n}{\cosh \chi_n - \cos(\omega - \theta_n)}$$

$$\chi_n = \ln r_n$$




$$D(\omega) = \frac{d\tau(\omega)}{d\omega} \propto \frac{1}{FSR^2}$$

Larger FSR \Rightarrow smaller dispersion; More stages \Rightarrow more dispersion




Four-Stage All-Pass Filter

*Approximation of
Linear group delay
across pass band*





Equi-ripple design



APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

REVIEW OF THIS MATERIAL DOES NOT IMPLY DEPARTMENT OF
DEFENSE INDORSEMENT OF FACTUAL ACCURACY OR OPINION

Four-Stage All-Pass Filter Experimental




APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED


REVIEW OF THIS MATERIAL DOES NOT IMPLY DEPARTMENT OF
DEFENSE INDORSEMENT OF FACTUAL ACCURACY OR OPINION

Dispersion vs. Bandwidth Tradeoff

25 GHz Channel Spacing





100 GHz Channel Spacing



APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

REVIEW OF THIS MATERIAL DOES NOT IMPLY DEPARTMENT OF
DEFENSE INDORSEMENT OF FACTUAL ACCURACY OR OPINION

All-Pass Filter - Effect of Finite Loss




APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

REVIEW OF THIS MATERIAL DOES NOT IMPLY DEPARTMENT OF
DEFENSE INDORSEMENT OF FACTUAL ACCURACY OR OPINION

Broadband All-Pass Filters


Basic Design




$$FSR \uparrow \Rightarrow R \downarrow \Rightarrow \Delta \uparrow$$




Achieving required coupling κ
practically not feasible



Multi-channel Dispersion Compensation



Constant dispersion compensation




Dispersion slope compensation

APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED


REVIEW OF THIS MATERIAL DOES NOT IMPLY DEPARTMENT OF DEFENSE INDORSEMENT OF FACTUAL ACCURACY OR OPINION

Thin-film All-Pass Filter

Single-stage Silica substrate (25 GHz FSR)



Package loss 0.3 dB




Gires-Tournois
Interferometer (GTI)

APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

REVIEW OF THIS MATERIAL DOES NOT IMPLY DEPARTMENT OF
DEFENSE INDORSEMENT OF FACTUAL ACCURACY OR OPINION



General Construction of an All-Pass Filter




This is an all-pass filter if:

1. $\det(M) = 1$
2. $M_{22} = M_{11}^*$

FSR determined by
feedback path delay

More General All-Pass Structures






$$\det(M) = 1$$

$$M_{11}^* = M_{22}M_{33} - M_{23}M_{32}$$

$$M_{22}^* = M_{11}M_{33} - M_{13}M_{31}$$

$$M_{33}^* = M_{22}M_{11} - M_{21}M_{12}$$



APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED


REVIEW OF THIS MATERIAL DOES NOT IMPLY DEPARTMENT OF DEFENSE INDORSEMENT OF FACTUAL ACCURACY OR OPINION



Simple Case



Directional coupler



*Single stage
all-pass filter*


Scaling problem:



Larger FSR \Rightarrow Smaller rings \Rightarrow Larger bend loss \Rightarrow Larger Δ material \Rightarrow Coupler gap too small



MZI-based APF




This design is no longer sensitive to the couplers

Equivalent to simple case, but with **tunable coupling**



Another solution



Vertical grating-assisted coupling




APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

REVIEW OF THIS MATERIAL DOES NOT IMPLY DEPARTMENT OF
DEFENSE INDORSEMENT OF FACTUAL ACCURACY OR OPINION



Nonlinear all-pass filters




$$\Phi_{eff} \sim \left(\frac{2\pi}{\lambda} n_2 IL \right) 4F^2$$

$$F \sim \frac{\tau_{max}}{T}$$

However, large F implies
small bandwidth




For ~ 1 ps timescales
requires very small rings
or disks ($\sim 1 \mu\text{m}$)



(Heebner and Boyd, *Opt. Lett.*, 1999)

Practical considerations



Vertical coupling

$R \sim 1 \mu\text{m}$
 $F \sim 30$
Cavity losses?



Summary

- *Ring resonators can be used as tunable optical phase equalizers*
- *Large bandwidth devices require many small rings*
- *Ring loss needs to be minimized*
- *Nonlinear micro rings may be used for fast all-optical switching*